

DC-D1223WX

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Vari-focal lens (f=3 - 9mm)
- micro SD / SDHC
- Two-way audio
- Alarm in / out
- Vandal proof / IP66 supports
- PoE (IEEE 802.3af Class 2), 12VDC
- Day and night (ICR)
- True wide dynamic range (WDR)
- Digital image stabilization (DIS)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO		
Image Sensor	1/2.8" CMOS	
Max. Resolution	1920 x 1080	
Scanning Mode	Progressive Scan	
Lens Type	Vari-focal	
Focal Length	f=3 - 9mm	
Aperture	F1.2 - 2.3	
Iris Control	DC Auto Iris	
Angular Field of View	Wide : 111.0° (H), 57.8° (V), 133.8° (D) Tele : 35.7° (H), 20.0° (V), 41.0° (D)	
Pan/Tilt Range	Pan: -167° ~ 167°, Tilt: 0° ~ 70°, Rotate: -176° ~ 176°	
Min. Illumination	Color : 0.005 lux @ F1.2 B/W : 0.0002 lux @ F1.2	
S/N Ratio	More than 45dB	
Dynamic Range	120dB (True wide dynamic range (WDR))	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter(1 ~ 1/5, 1/7.5, 1/15)	
Day and Night	IR cut filter with auto switch	
IR Distance (LEDs)	-	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR/3DNR	
Backlight Compensation	-	
Image Stabilizer	Yes (DIS)	
Privacy Masking	16 Zones	
Intelligent Video	Video Motion Detection, Face Detection, Active Tampering Alarm	
Video Out	1 Terminal Block	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.264 (MP), M-JPEG	
Bitrate Control	H.264 - VBR	
Max. Frame Rate	60fps : 1920 x 1080 30fps : 1920 x 1080(WDR)	
Audio Compression	G.726, G.711	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240	1920x1080, 1280x720, 704x480, 352x240
Multi-video Streaming	Quadruple Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100/1000BASE-T)	
Edge Storage	micro SD / SDHC	
ALARM AND EVENT		
Trigger Event	Motion Detection, Face Detection, Alarm in, Tampering	
Event Buffering (Pre and Post)	Yes (Up to 60MB)	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea / Line-out 1ea	
Alarm In/ Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Proof Casing	IK10	
Outdoor Ready	IP66	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 2)	
Power Consumption	5.16W	
Approvals	FCC, CE, KC	
MECHANICAL		
Dimensions	Ø160mm x 112mm (Ø6.3" x 4.41")	
Weight	0.87 kg (1.92 lb)	

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

