

Full HD 12x PTZ Compact Camera

DC-S6261X-A

NEW



- Easy Installation with DirectIP NVR
- Full HD (1080p) Resolution
- AF optical zoom lens (f = 5.3 - 64 mm), 12x zoom
- micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
- PoE (IEEE 802.3af Class 3), 12V DC
- Alarm In / Out
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- Electronic Image Stabilization (EIS)
- Supports ONVIF



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	AF Zoom Lens
Focal Length	f = 5.3 - 64 mm (12X)
Aperture	F1.6 - 2.8
Iris Control	DC Auto IRIS (with Hall Sensor)
Angular Field of View	Wide : 58.2°(H), 34°(V), 65.3°(D) Tele : 4.83°(H), 2.8°(V), 5.7°(D)
Min. Illumination	Color : 0.1 Lux @ F1.6 B/W : 0.01 Lux @ F1.6
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	-
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical
Image Stabilizer	Yes (EIS)
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm
Auto Tracking	No
Video Out	-
PAN / TILT / ROTATE	
Pan Range	360° (Endless)
Pan Speed	0.02~150°/sec (Preset 150°/sec)
Tilt Range	180° (0~180°)
Tilt Speed	0.02~150°/sec (Preset 150°/sec)
Preset	256ea
NETWORK	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.264 - CBR / VBR, H.265 - CBR / VBR
Audio Compression	-
Two-way Audio	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30ips : 1920 x 1080 (WDR)
Supported Resolution	1920 x 1080, 1280 x 720, 640 x 360, 352 x 240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio In / Out	-
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	-
Outdoor Ready	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	12VDC, PoE IEEE 802.3af (Class 3)
Power Consumption	12VDC, 9.2W / PoE (IEEE 802.3af Class 3), 10W
Approvals	FCC, CE(50130-4), KC, UL
MECHANICAL	
Dimensions	Ø155 mm x 158.1 mm (Ø6.1" x 6.22")
Weight	1.0 kg (2.20lb)



DIMENSIONS



(Unit - mm)

ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

