

# DC-T4517WRX 4.3mm

## H.265 5M Bullet Camera / NDAA Compliant



- Easy installation with DirectIP NVR
- PoE (IEEE 802.3af Class 3)
- True wide dynamic range (WDR)
- H.265 and Intelligent Codec
- IR LED (Distance : 20 m / 65.6 ft)
- Day and night (ICR)
- Affordable 5MP High Resolution
- Fixed-focal lens
- Supports ONVIF

### SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	4.3mm
Aperture	F1.6
Iris Control	Fixed Iris
Angular Field of View	80o(H) 56.7o(V) 106.9o(D)
Min. Illumination	COLOR : 0.15 lux @ F1.6 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 - 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	-
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960x 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, SMTP, FEN, mDNS, Upnp, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLSrec)	Yes (Up to 60MB)
Alarm and Event	
Trigger Event	Motion Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP66
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE IEEE 802.3af (Class 3)
Power Consumption	PoE, IEEE 802.3af (Class 3), 6.5W
Approval	FCC, CE, KC
Mechanical	
Dimensions	70mm X 65mm X 197.5mm (2.76" X 2.56" X 7.78")
Weight	0.4kg (0.88lb)



### PRODUCT IMAGE



### DIMENSIONS

(Unit - mm)

