

DC-Z1263

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- AF optical zoom lens (f=4.7 - 84.6mm), 18x zoom
- SD/SDHC
- Two-way audio
- Alarm in / out
- PoE (IEEE 802.3af class 0), 12VDC, 24VAC
- Day and night (ICR)
- Supports ONVIF



SPECIFICATIONS

VIDEO																													
Image Sensor	1/2.8" CMOS																												
Max. Resolution	1920 x 1080																												
Scanning Mode	Progressive Scan																												
Lens Type	AF Zoom Lens																												
Focal Length	f=4.7 - 84.6mm																												
Aperture	F1.6 - 2.8																												
Iris Control	DC Auto Iris																												
Angular Field of View	Wide : 61.2° (H), 35.6° (V), 68.9° (D) Tele : 3.6° (H), 2.1° (V), 4.1° (D)																												
Min. Illumination	Color : 0.1 lux @ F1.6 B/W : 0.004 lux @ F1.6																												
S/N Ratio	31.2dB																												
Dynamic Range	74.7dB																												
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1/7.5,1/15)																												
Day and Night	IR cut filter with auto switch																												
IR Distance (LEDs)	-																												
Image Setting	Configurable Exposure, White Balance, Sharpness																												
Digital Noise Reduction	Configurable 2DNR																												
Backlight Compensation	On / Off/ HSBLC																												
Mirroring / Pivot	Horizontal / Vertical																												
Image Stabilizer	-																												
Privacy Masking	16 Zones																												
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone																												
Video Out	1 RCA																												
NETWORK																													
	<table border="1"> <thead> <tr> <th>DirectIP Mode</th> <th>Compatibility Mode</th> </tr> </thead> <tbody> <tr><td>Video Compression</td><td>H.264 (MP), M-JPEG</td></tr> <tr><td>Bitrate Control</td><td>H.264 - CBR / VBR</td></tr> <tr><td>Max. Frame Rate</td><td>30fps : 1920 x 1080</td></tr> <tr><td>Audio Compression</td><td>G.726, G.711</td></tr> <tr><td>Two-way Audio</td><td>Yes</td></tr> <tr><td>IP Camera Protocol</td><td>DirectIP</td></tr> <tr><td>Supported Resolution</td><td>1920x1080, 1280x720, 704x480, 640x360, 352x240</td></tr> <tr><td>Multi-video Streaming</td><td>Triple Streaminging</td></tr> <tr><td>Network Protocols</td><td>DirectIP Protocol</td></tr> <tr><td>Security</td><td>SSL Encryption</td></tr> <tr><td>Remote Access Client</td><td>DirectIP NVR connection</td></tr> <tr><td>Ethernet</td><td>RJ45 (10/100BASE-T)</td></tr> <tr><td>Edge Storage</td><td>SD (SDHC)</td></tr> </tbody> </table>	DirectIP Mode	Compatibility Mode	Video Compression	H.264 (MP), M-JPEG	Bitrate Control	H.264 - CBR / VBR	Max. Frame Rate	30fps : 1920 x 1080	Audio Compression	G.726, G.711	Two-way Audio	Yes	IP Camera Protocol	DirectIP	Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240	Multi-video Streaming	Triple Streaminging	Network Protocols	DirectIP Protocol	Security	SSL Encryption	Remote Access Client	DirectIP NVR connection	Ethernet	RJ45 (10/100BASE-T)	Edge Storage	SD (SDHC)
DirectIP Mode	Compatibility Mode																												
Video Compression	H.264 (MP), M-JPEG																												
Bitrate Control	H.264 - CBR / VBR																												
Max. Frame Rate	30fps : 1920 x 1080																												
Audio Compression	G.726, G.711																												
Two-way Audio	Yes																												
IP Camera Protocol	DirectIP																												
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240																												
Multi-video Streaming	Triple Streaminging																												
Network Protocols	DirectIP Protocol																												
Security	SSL Encryption																												
Remote Access Client	DirectIP NVR connection																												
Ethernet	RJ45 (10/100BASE-T)																												
Edge Storage	SD (SDHC)																												
IP Camera Protocol	DirectIP																												
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240																												
Multi-video Streaming	Triple Streaminging																												
Network Protocols	DirectIP Protocol																												
Security	SSL Encryption																												
Remote Access Client	DirectIP NVR connection																												
Ethernet	RJ45 (10/100BASE-T)																												
Edge Storage	SD (SDHC)																												
ALARM AND EVENT																													
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone																												
Event Buffering (Pre and Post)	Yes (Up to 60MB)																												
Event Notification	Remote S/W, Email (With Image)																												
Audio In / Out	Line-in 1ea / Line-out 1ea																												
Alarm In/ Out	Input 1ea / Output 1ea																												
ENVIRONMENTAL																													
Vandal Proof Casing	-																												
Outdoor Ready	-																												
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)																												
Operating Humidity	0% - 90%																												
ELECTRICAL																													
Power Source	12VDC, 24VAC, PoE (IEEE 802.3af class 0)																												
Power Consumption	6W																												
Approvals	FCC, CE (50130-4), KC																												
MECHANICAL																													
Dimensions	77.8mm x 75mm x 190.1mm (3.07" x 2.96" x 7.49")																												
Weight	0.71 kg (1.57 lb)																												

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

