

# DD-1116

- Specialized in DirectIP NVR
- Supports DirectIP NVR
- Supports HDMI, VGA, CVBS port
- Up to 4 channel Full HD display
- Up to 16 channel real-time display



## SPECIFICATIONS

DECODER	
Video Compression	H.264
Video Input	16ch IP
Video Input resolution	up to 3MP
Supported Devices	DirectIP NVR
Video Outputs	1 HDMI, 1 VGA, 1 CVBS
Display Resolution	HDMI, VGA : 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 CVBS : 640x480
Display Speed	Up to 480ips
Max. Network Throughput	48Mbps
Network Connection	Gigabit Ethernet x 1
GENERAL	
Dimensions (W x H x D)	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Weight	0.84kg (1.85lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
PoE (Class)	Yes (IEEE 802.3af Class 0)
Power Input	12VDC, PoE
Power Consumption	12V, 0.9A, 10.8W PoE, IEEE 802.3af(Class 0)
Approvals	FCC, CE

## DIMENSIONS

(Unit - mm)

