

VW-F552

SPECIFICATIONS

PANEL	
Type	LED
Screen Size	55 Inch
Active Display Area	1,209.6mm(H) x 680.4mm(V)
Max. Resolution	1920 x 1080 @ 60Hz
Panel Technology	IPS(In-Plane Switching)
Anti Glare	Yes
Pixel Pitch	0.63mm(H) x 0.63mm(V)
Brightness	500cd/m ²
Contrast Ratio	1400:1
Aspect Ratio	16:9
Viewing Angle(H/V)	178°/178°
Display Color	1.07 Billions
H-Scanning Frequency	31~67Khz
V-Scanning Frequency	49~60Khz
Response Time (G2G)	<8ms
Refresh Rate	60Hz
Panel Life Time	50,000Hours
INTERFACE	
Hybrid(AHD,TVI,CVI, CVBS) In/Out	-
HDMI In	2(HDMI 2.0 x 1, 1.4 x 1)
Display Port	1(1.2 Ver.)
VGA Input	1
DVI Input	1/1*
Audio In/Out	-
BNC Video In/Out	-
S-Video In/Out	-
Component Y/pb/Pr In	-
S/PIDF Output	-
RS232 In/Out	1/1(RJ45)
USB	1
GENERAL	
Outline Dimension(WxHxD)	1,213.4mmx684.2mmx121.85mm (47.77"x26.94"x4.79")
Bezel width (Spec. for VideoWall)	3.5mm(Bezel to Bezel)
Net Weight/Gross Weight	27.5Kg(60.62lb)/35Kg(77.16lb)
Material/Color	Metal / Black
Warranty-Parts/Labor	3 Year / 3 Year
MTBF	50,000 Hours
Power Supply	AC100~240V(50/60Hz)
Power Consumption - Typical	200W
Power Consumption - Stand by	<0.5W
Power Savings(DPMS)	Yes
Operating Temperature	0°~40°C(32°F~104°F)
Storage Temperature	-10°~60°C(14°F~140°F)
Built-In Speaker	-
Remote Control	Yes
VESA Mount Size	600mm x 400mm / M6 x 12 Screws
Operation Hours	24/7
Prevent Burn-In	Yes
OPTIONS	
Android Board	-
OPS	-
EXTERNAL CONTROLS	
IR Sensor(For Remote Control)	Built-in
Serial In/Out	RS232-C Daisy Chain
USB	For Firmware Update

* * DVI Port Pass through up to 10 X 10



DIMENSIONS

(Unit - mm)

