DA-JB2200 INSTALLATION MANUAL





This manual is intended for users of the DA-JB2200 ceiling mounting bracket. It includes instructions for mounting the DA-JB2200 ceiling mounting bracket to a ceiling.



- This bracket is intended to be used with a specific model of camera.
 Do not use it with other models of cameras except for those approved by the dealer or distributor.
- This installation should be performed by a qualified service personnel in conformance to all local codes.
- You may need to reinforce the ceiling. If the ceiling is not strong enough to support the camera, the camera may fall.
- · Do not use this product for other purposes.

Mounting

Mount the bracket to the ceiling as follows:

- Insert cables from external devices, network and power adapter to the sponge and bracket. If you have a PT 1/2 inch pipe, remove the PT 1/2 inch cap and make the cables go through the pipe. Assemble the removed PT 1/2 inch cap to the bracket's ceiling hole. Ask your dealer or distributor for details about connecting a pipe.
- 2 Mount bracket to the ceiling by using the provided anchors, rubbers, and screws.




Make sure that a rubber is attached between bracket and a screw.

PT 1/2 inch CAP Bracket Rubber Ceiling Hole

Connect your camera to the bracket as follows:

- 3 Screw the camera body onto bracket.
- 4 Screw the camera dome cover onto the camera body.
- 5 Turn on power.



Dimensions

Unit: mm (inch)

