



IDIS Covert Modular Camera



NETWORK CAMERAS

	Covert Modular Camera	
	DC-V3213XJ-4.3mm	DC-V3213XJ-2.5mm
Model Name	NEW 	NEW 
Image Sensor	1/2.9" CMOS	1/2.9" CMOS
Max. Resolution	1920 x 1080	1920 x 1080
Lens Type	Fixed-focal Sharp-corn	Fixed-focal Board Type
Focal Length	f = 4.3mm	f = 2.5mm
Aperture	F2.0	F2.0
Iris Control	Fixed Iris	Fixed Iris
Angular Field of View	83° (H), 47° (V), 95° (D)	132° (H), 70° (V), 150° (D)
Min. Illumination	Color : 0.1 Lux B/W : 0.01 Lux	Color : 0.1 Lux B/W : 0.01 Lux
Dynamic Range	120dB (True WDR)	120dB (True WDR)
Day and Night	Auto / On / Off / Schedule	Auto / On / Off / Schedule
IR Distance (LEDs)	N/A	N/A
Video Out	-	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported
Audio Compression	G.726, G.711	G.726, G.711
Max. Frame Rate	30ips : 1920 x 1080	30ips : 1920 x 1080
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	micro SD / SDHC / SDXC	micro SD / SDHC / SDXC
Trigger Event	Motion Detection Alarm In Audio Detection Tampering Trip Zone	Motion Detection Alarm In Audio Detection Tampering Trip Zone
Audio In / Out	Line-in 1ea / Line-out 1ea (Terminal Block)	Line-in 1ea / Line-out 1ea (Terminal Block)
Alarm In / Out	Input 1ea / Output 1ea (Terminal Block)	Input 1ea / Output 1ea (Terminal Block)
Vandal Proof Casing	N/A	N/A
Outdoor Ready	N/A	N/A
Operating Temperature	-10°C ~ +50°C (-14°F ~ +122°F) *Starting Up at Above 0°C (32°F)	-10°C ~ +50°C (-14°F ~ +122°F) *Starting Up at Above 0°C (32°F)
Power Source	12VDC, PoE (IEEE 802.3at Class 4)	12VDC, PoE (IEEE 802.3at Class 4)
Power Consumption	4.08W	4.08W