

# DR-1508P

## DirectIP 1500 Series Full HD Recorder /NDA Compliant



- Total incoming throughput 100Mbps
- Easy to install, set-up, and play with DirectIP cameras
- Up to 240ips 8MP real-time recording
- Built-in 8 channel PoE Switch
- Up to 240ips live display
- Supports one click network configuration through FEN service

### SPECIFICATIONS

VIDEO	
Video Inputs	8 IP Channels
Max. Incoming Throughput	100Mbps
Supported Camera	DirectIP
Video Outputs	1 HDMI, 1 VGA
Display Resolution	1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 240ips
Digital Zoom	x2 ~ x12
RECORDING	
Max. Throughput	40Mbps, 240ips@8MP
Recording Resolution	Up to 8MP (Depending on IP Camera)
Compression	H.265, H.264
Recording Mode	Time-lapse, Event, Pre-event, Panic
Trigger Events	Motion Detection, Trip-zone, Tampering, Video Loss, Etc.
PLAYBACK	
Performance	4ch Full HD Synchronous Playback
Search Mode	Time-lapse, Event Log
Digital Zoom	x2 ~ x12
STORAGE	
HDD	SATA x1, (Up to 4TB Capacity, 3.5)
NETWORK	
Client Connection	Fast Ethernet (Client) x1
Video In Connection	Fast Ethernet (IP Camera) x8
Transmission Speed	20Mbps
Camera Power	PoE (IEEE 802.3at Class 4) Supported 8 Ports, 50W
Remote Data Export	IDIS Player, AVI, JPG
Event Notification	Email (MP4), Callback to Remote S/W, Push Notification (IDIS Mobile)
Two-way Audio	No
Client Viewer	IDIS Center, IDIS Mobile, IDIS Solution Suite, IDIS Web(web.idisglobal.com only)
INTERFACE	
Audio In/ Out	No
Alarm In / Out	No
Serial Interface	No
USB	USB2.0 x 2
User Interface	Mouse
GENERAL	
Operating System	Embedded Linux
UNIT Dimensions (W x H x D)	205mm x 44.5mm x 216.4mm (8.07" x 1.75" x 8.52")
Unit Weight	1.38kg (3.04lb) (with 4TB HDD)
Working Temperature	0°C to 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Power Consumption	NVR: 54-56V=, 1.28-1.24A, Max. 69W, PSE : Max. 50W
Approvals	KC, CE, FCC



### PRODUCT IMAGE



### DIMENSIONS

