

DV-1104



- Specialized in DirectIP NVR
- Supports 4 channel IP Camera
- Supports People Counting
- Supports Heatmap
- Supports Queue Management

SPECIFICATIONS

DECODER	
Video Compression	H.264, H.265
Video Input	4ch IP
Supported Devices	DR-6308P, DR-6316PS, DR-6332PS, DR-8364 DR-8364D, DR-2304P, DR-2308P, DR-2316P, DR-8416, DR-8432, DR-8432D
Max. Network Throughput	20Mbps
Newtork Connection	Gigabit Ethernet x 1
VA Support	People Counting Heatmap Queue Management (Max. 3 queues)
GENERAL	
Dimensions (W x H x D)	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Weight	0.74kg (1.6lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
PoE (Class)	Yes (IEEE 802.3af Class 3)
Power Source	12VDC, PoE
Power Consumption	12V=, 0.55A, 6.6W PoE, IEEE 802.3af(Class 3)
Approvals	FCC, CE, KC

Analytic Reports Reports and graphs

Report with graphs and thumbnails by setting a time period. Periodical analysis for each feature is available through the VMS "VA report" tab. You can check hourly/daily/weekly/monthly data in detail by simply entering a date and time. The data from the People Counting, Queue Management, and Heat Map functions can be reviewed individually or collectively.

