DV-3200-B

Al in the Box / NDAA Compliant

- · AI in the BOX with IDIS Solution Suite
- [IDLA] Superior Accuracy deep-learning engine
- Compatible with IDIS Deep-Learning Analytics (IDLA)
- [IDLA] Object classification suitable for CCTV application
- 2U rack mount chassis
- [IDLA] Simple configuration and Zero calibration

SPECIFICATIONS

SYSTEM	
IDIS Solution Suite	Compatible with IDLA VA Service
Network Connection	2 GbE RJ-45 Ports (1000Base-T)
Channels available for Analytics	Up to 64ch in condition of 640x360@5ips video input
IDLA Processing Unit	NVIDIA A2000, 6GB
Operating System	Microsoft Windows 10 lot Enterprise
SSD	250GB(M.2 Type) for OS and ISS VA Service
Processor	Intel I5-10500, 3.1GHz
Memory	DDR4 PC-25600, 16GB
Video Outputs	2 HDMI
USB	6 (2 Front USB 2.0 4 Back (3 USB 3.0 TYPE-A 1 TYPE-C))
MECHANICAL	
Form Factor	2U RACK Mount Chassis
Unit Dimension (W x H x D)	482.6mm x 88mm x 523.5mm (19" x 3.5" x 20.6")
Unit Weight	11.8kg (26.0 lbs)
ELECTRICAL	
Power Input	100-240V~, 50/60 Hz, 6.0 - 3.0A
Power Supply	Single Power
Power Consumption	270W
ENVIRONMENTAL	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	0% to 90%
ACCESSORIES SUPPLIED	
Power Cord	1
General	
Certifications	FCC, CE, CB, UL, KC











PRODUCT IMAGE



DIMENSIONS

