

Full HD Flush Dome Camera

DC-D3233FX-N

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Motorized Vari-focal lens (f=2.8 - 12mm)
- micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)
- Two-way audio
- Alarm in / out
- PoE (IEEE 802.3af Class 2), 12V DC
- Day and night (ICR)
- True wide dynamic range (WDR)
- Low light enhancer
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO		
Image Sensor	1/3" CMOS	
Max. Resolution	1920 x 1080	
Scanning Mode	Progressive Scan	
Lens Type	Motorized Vari-focal	
Focal Length	f=2.8 - 12mm	
Aperture	F=1.6 - 2.7	
Iris Control	P-Iris	
Angular Field of View	Wide : 98° (H), 52° (V), 116° (D) Tele : 33° (H), 18.5° (V), 37.9° (D)	
Pan / Tilt Range	Pan : -176° ~ 176°, Tilt : 0° ~ 66°, Rotate : -90° ~ 90°	
Min. Illumination	Color : 0.1 Lux @ F1.6 B/W : 0.01 Lux @ F1.6	
Dynamic Range	120dB (True WDR)	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1 ~ 1/5, 1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)		
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR / 3DNR	
Backlight Compensation	On / Off / HSBC	
Image Stabilizer	-	
De-fog	On / Off	
Privacy Masking	8 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Video Out	1 BNC (Accessory)	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.265, H.264 (MP), M-JPEG	
Intelligent Codec	Supported	
Bitrate Control	H.264 - CBR / VBR, H.265 - CBR / VBR	
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	30fps : 1920 x 1080 (WDR)	60fps : 1920 x 1080 30fps : 1920 x 1080 (WDR)
Supported Resolution	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240
Multi-video Streaming	Quadruple Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100 BASE-T)	
Recording Session Buffer (NLTRec)	Yes (Up to 60MB)	
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)	
ALARM AND EVENT		
Trigger Event	Motion Detection, Audio Detection, Alarm In, Tampering, Trip Zone	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea / Line-out 1ea	
Alarm In / Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Proof Casing		
Outdoor Ready		
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 2)	
Power Consumption	5.8W	
Approvals	FCC, CE	
MECHANICAL		
Dimensions	Ø174mm x 122.4mm (Ø6.85" x 4.82")	
Weight	0.71kg (1.56lb)	

DIMENSIONS

(Unit - mm)

