

## DD-1216

- Supports DirectIP™ NVR
- Supports IDIS IP Camera
- Supports HDMI, VGA, CVBS port
- Up to 480ips live display



### SPECIFICATIONS

DECODER	
Video Compression	H.264, H.265
Video Input	16ch IP
Video Input Resolution	Up to 12MP
Supported Devices	DirectIP NVR, IDIS IP Camera
Video Outputs	1 HDMI, 1 VGA, 1 CVBS
Display Resolution	HDMI : 3840x2160, 2560x1440, 1920x1200, 1920x1080, 1680x1050, 1600x1200 VGA : 2560x1440, 1920x1200, 1920x1080, 1680x1050, 1600x1200 CVBS : 720x480(NTSC), 720x576(PAL)
Display Speed	Up to 480ips
Max. Network Throughput	90Mbps
Network Connection	Gigabit Ethernet x 1
GENERAL	
Dimensions (W x H x D)	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Weight	0.78kg (1.72lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
PoE (Class)	Yes (IEEE 802.3af Class 0)
Power Input	12VDC, PoE
Power Consumption	12V=, 1.03A, 12.7W PoE, IEEE 802.3af(Class 3)
Approvals	FCC, CE, KC

### DIMENSIONS

(Unit - mm)

