## **DV-1304-A**

## 4ch Al in the box

· Specialized in DirectIP $^{\text{TM}}$  NVR

4 IP Channels

DirectIP NVR

H.265, H.264

0% ~ 90%

48V=, PoE

FCC, CE, KC

0.88kg (1.94 lb)

0°C to 40°C (32°F to 104°F)

200mm x 44mm x 157.6mm (7.9" x 1.7" x 6.2")

Object Detection, Intrusion, Loitering, Line Crossing, Face Detection

48V=, 0.8A, 38.4W POE, IEEE 802.3at(Class 4), 25W DC OUTPUT : 48V=, 0.35A MAX

100M Ethernet x 1 (100Base-TX) with PD 100M Ethernet x 1 (100Base-TX) with PSE (PSE need Adaptor)

- · Supports Object Detection
- · Supports Line Crossing

**SPECIFICATIONS** 

Video Inputs

VA Support

**Supported Device** 

**Video Compression** 

Network Connection

Operating Temperature

Operating Humidity

**Power Consumption** 

Unit Dimensions (W x H x D)

Power Input

Approval

Unit Weight

- · Supports 4ch IP Camera
- · Supports Intrusion
- · Supports Face Detection

- Supports the most advanced IDIS Deep-Learning
- Analytics (IDLA)
- · Supports Loitering
- Generating real-time event notifications with high
- accuracy









## **PRODUCT IMAGE**



## DIMENSIONS



