

TC-B1202

- Full HD (1080p) resolution
- C/CS mount lens
- Day and night (ICR)
- WDR (15fps)
- Motion detection
- De-fog
- HSBLC
- OSD control over coax



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" Sony 2Mega Exmor CMOS Sensor
Effective Pixels	1984 (H) x 1105 (V), 2.19MP
Total Pixels	2000 (H) x 1121 (V), 2.24MP
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Optional (C/CS Mount Lens)
Iris Control	DC Auto Iris / Manual Iris
Min. Illumination	Color : 0.3 Lux @ F1.4 (AGC MAX) B/W : 0.1 Lux @ F1.4 (AGC MAX) 0.001 Lux @ F1.4 (AGC MAX, Sens-up Max)
S/N Ratio	More than 50dB
Electronics Shutter Speed	Auto / Manual (1/30, 1/25Sec ~ 1/30000Sec) / Flicker
Day and Night	Yes (ICR)
Video Out	1 HD BNC, 1 SD BNC
FUNCTION	
AGC	0 ~ 20 Level Adjustable
Brightness	0 ~ 20 Level Adjustable
Sens-up	Off / x2 ~ x32
WDR	Off / On (Low, Middle, High / 15 Frame)
BLC	Off / On
HSBLC	1 ~ 20 Level Adjustable (All Day / Night Only)
ACE (D-WDR / ATR-EX)	Off / Low / Middle / High
Motion Detection	Off / On (4 Zone)
Privacy Masking	Off / On (16 Zone)
Day and Night	Auto (AGC) / Color / B/W / Extern
Smart IR (IR Optimizer)	-
White Balance	Auto (2,500K ~ 9,500K) / AWB (1,800K ~ 10,500K) / AWC→Set / Manual
Digital Noise Reduction	2D + 3DNR (Off / Low / Middle / High)
Mirror	Mirror, V-flip
D-ZOOM (EZOOM)	x1 ~ x8
Sharpness	0 ~ 20 Level Adjustable
De-fog	Off / On
GAMMA Correction	R = 0.45 ~ 0.65
Lens Shading (LSC)	Off / On
ENVIRONMENTAL	
Outdoor Ready	-
Storage Temperature	-20°C ~ +60°C (-4°F ~ +140°F) (Humidity : 0% ~ 95%)
Operating Temperature	-10°C ~ +50°C (14°F ~ +122°F) (Humidity : 0% ~ 90%)
ELECTRICAL	
Power Source	12VDC, 24VAC
Power Consumption	2.64W
MECHANICAL	
Dimensions (W x H x D)	58mm x 52mm x 123mm (2.29" x 2.05" x 4.85")

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



DA-BH1100



DA-WM1500

ACCESSORIES CONFIGURATION TREE



DA-BH1100
Box Housing



DA-WM1500
Wall Mount